

AS 207

MEMBRANE SCALE INHIBITOR

DESCRIPTION:

AS 207 is a general-purpose scale inhibitor for use in reverse osmosis systems. AS 207 contains a combination of scale inhibiting chemistry to prevent the precipitation of dissolved solids on the membrane surface. AS 207 also contains a high-performance terpolymer to aid in flushing contaminants and foulants from the membrane and feedwater spacer surfaces.

AS 207 is specifically designed to provide control of calcium and other metal salts by acting as a crystal modifier and threshold inhibitor. AS 207 may be used with both thin film and cellulose acetate membranes.

GENERAL APPLICATION:

AS 207 should be injected into the feedwater line of the reverse osmosis unit just before the cartridge filter. AS 207 should be added at a rate of 15 - 100 ppm of product as received. It may also be diluted for ease of feeding in some systems.

ADVANTAGES:

- Especially effective against iron and manganese deposition
- Inhibits deposition of calcium phosphate
- Effective removal of contaminants and foulants from membrane and spacer surfaces
- For use on both thin film composite and cellulose acetate membranes

Typical Product Characteristics

AppearanceLight Amber Liquid
Density at 25° C.....1.07 – 1.09
Weight per US gallon ...8.99 lbs/gal
pH of product6 - 7

SAFETY & HANDLING:

Improper handling of this product can be injurious to workers. Observe all safety precautions shown on the label and Material Safety Data Sheets. Wear proper protective equipment listed on the MSDS. Follow the instructions of your KML Representative in the proper use of this product.

PACKAGING:

AS 207 is available in non-returnable, 55 gallon, DOT approved plastic containers.

