

Amercoat PS-253

EPOXY FLOOR SEAL

DESCRIPTION:

PS-253 is an Epoxy Ester coating designed to enhance the appearance and lend chemical resistance to concrete floors.

GENERAL APPLICATIONS:

PS-253 may be rolled, brushed or mopped on. The preferred method is a lamb's wool applicator. Any form of spray application yields excellent results as well. PS-253 should not be diluted. For clean up, use mineral spirits.

SAFETY & HANDLING:

Improper handling of PS-253 can be injurious to workers. May cause transient irritation to eyes. Flush with large amounts of water. If irritation persists, consult with physician. Avoid breathing vapors, in confined areas, use proper respirator.

Observe all safety precautions shown on the label and in the Material Safety Data Sheet. Wear proper protective equipment listed on the MSDS. Follow the instructions of your KML Representative in the proper use of this product.

ADVANTAGES:

- Medium-high solids, self-leveling properties
- Two-coat application designed specifically to adhere to and protect all substrates
- Resistant to most solvents
- Quick dry time of less than 1 hour
- Hard long lasting resin, mar resistant

Typical Product Characteristics

Appearance	Clear, Amber liquid
Odor	Mineral Spirits
Specific Gravity	0.84
pH	NA
Flash Point	130°F
VOC Content	5.0lbs./gal.

STORAGE:

PS-253 should be stored away from strong oxidizing agents. Store away from heat, sparks and open flame, product is flammable.

