

# AQUASOL

## Paint Shop Coating

### DESCRIPTION:

AQUASOL is clear, water based, water-soluble dry coating. It is formulated for use as a temporary booth coating for the interior surfaces of spraybooth. If portions of the dry coating enter into the booth water system, there will be no interference of water scrubbing areas of the spray booth. AQUASOL fully dissolves under water pressure, which aids in the removal of the coating.

### GENERAL USE

#### INSTRUCTIONS:

AQUASOL is designed to be sprayed, rolled or brushed on as received. Apply AQUASOL with a tip pressure of 1,500 psi and a tip orifice of .0020. A power roller may be used for more effective application when rolling.

#### ADVANTAGES:

- May be rinsed with water
- One coat application designed specifically to provide good protection
- Fast dry time, approximately one hour

- Will not generate foam if introduced into paint sludge system

### Typical Product Characteristics

Appearance ....	Clear, Odorless Liquid
Flash Point .....	None
Sp. Gravity .....	1.01
pH .....	8.0
Packaging .....	55 Gallon Drums 5-Gallon Pail

### SAFETY AND HANDLING:

AQUASOL may cause transient irritation to eyes. Flush with large amounts of water, if irritation persists consult with physician. Observe all safety precautions shown on the label and Material Safety Data Sheets. Wear proper protective equipment listed on the MSDS. Follow the instructions of your KML Representative in the proper use of this product.

AQUASOL should be stored away from strong oxidizing agents and strong acids.

