

AQUASOL SP

PAINT SHOP COATING

DESCRIPTION:

AQUASOL SP is a clear, water based, water-soluble peelable coating. Product is designed to serve as a temporary booth coating for the interior surfaces of spraybooth.

GENERAL USE

INSTRUCTIONS:

AQUASOLSP may either rolled, sprayed or brushed on. A power roller may be used for more effective application. For spray application: use min. 2,000 psi with a .0017 - .0025" orifice. Approximate coverage is 15 mils (wet). Product is not intended to be diluted. For clean-up, rinse with fresh water.

Typical Product Characteristics

Appearance	Clear Liquid
Odor.....	NA
Sp. Gravity	1.12
pH of Product.....	7.6 - 8.6
V.O.C. (lbs./gal.)	0.6

ADVANTAGES:

- May be either peeled or rinsed with water.
- One coat application designed specifically to provide good protection.
- Fast dry time; approximately one hour.
- Will not generate foam if introduced into the paint sludge system.

SAFETY AND HANDLING:

AQUASOL SP may cause transient irritation eyes. Flush with large amounts of water, if irritation persists, consult with physician. AQUASOL SP should be stored away from strong oxidizing agents and strong acids.

Improper handling of this product can be injurious to workers. Observe all safety precautions shown on the label and Material Safety Data Sheets. Wear proper protective equipment listed on the MSDS. Follow the instructions of your KML Representative in the proper use of this product.

