

## **BWT-1010**

### **ALKALINITY SUPPLEMENT**

#### **DESCRIPTION:**

BWT-1010 is a liquid hydroxide alkaline compound. BWT-1010 should be used as a supplement to a balanced water treatment program where additional OH alkalinity is required.

#### **GENERAL APPLICATIONS:**

Dosages will vary depending upon the alkalinity and hardness of the boiler feedwater. For optimum results, the recommendations of your KML Technical Representative should be followed.

#### **SAFETY & HANDLING:**

Improper handling of this product can be injurious to workers. Observe all safety precautions shown on the label and in the Material Safety Data Sheet. Wear proper protective equipment listed on the MSDS. Follow the instructions of your KML Representative in the proper use of this product.

#### **ADVANTAGES:**

- Provides for independent control of boiler OH alkalinity level
- Helps control scale formation
- Elevates boiler water pH for corrosion inhibition
- Formulated for use as a boiler water additive in FDA & USDA Application

#### **Typical Product Characteristics**

Appearance .....Clear viscous liquid  
Density at 25°C .....1.10 – 1.12 g/ml  
Weight per US gallon .....9.3 lbs./gal  
pH of product .....> 12.5

#### **PACKAGING:**

BWT-1010 is available in non-returnable, DOT approved 55-gallon plastic drums.

