

BWT-205H

SCALE INHIBITOR

DESCRIPTION:

BWT-205H is a liquid polymeric sludge conditioner. It is recommended for use as an adjunct to standard steam boiler treatments when additional sludge conditioning is required. BWT-205H may also be used for the removal of “scale-like” deposits.

GENERAL APPLICATIONS:

BWT-205H should be applied at a rate of one pint per every 1,000 gallons of make-up water. This dosage can be slightly higher or lower, depending upon the quality of make-up water and the amount of sludge conditioning that is required. For optimum results, the recommendations of your KML Technical Representative should be followed.

PACKAGING:

BWT-205H is available in non-returnable, DOT approved 55, 30, and 15-gallon plastic drums and 5-gallon pails.

ADVANTAGES:

- Provides excellent scale inhibition, ensuring maximum heat transfer efficiency
- Effective treatment for on-line descaling of “scale-like” deposits
- Formulated for use as a boiler water additive in FDA & USDA Applications
- Simple control test

Typical Product Characteristics

AppearanceLight yellow liquid
Density at 25°C1.07 - 1.09 g/ml
Weight per US gallon9.0 lbs./gal.
pH of product> 11.5

SAFETY & HANDLING:

Improper handling of this product can be injurious to workers. Observe all safety precautions shown on the label and the Material Safety Data Sheet. Wear proper protective equipment listed on the MSDS. Follow the instructions of your KML Representative in the proper use of this product.

