

BWT-209

STEAM BOILER TREATMENT

DESCRIPTION:

BWT-209 is a chemically balanced boiler water treatment. It is recommended for use as a main component of a total water treatment program where the boiler feedwater is relatively soft. BWT-209 contains polymeric sludge conditioners, chelating agents, an oxygen scavenger, and a hydrate alkalinity builder.

GENERAL APPLICATIONS:

Dosages will vary depending upon the temperature, alkalinity and hardness of the boiler feedwater. For optimum results, the recommendations of your KML Technical Representative should be followed.

SAFETY & HANDLING:

Improper handling of this product can be injurious to workers. Observe all safety precautions shown on the label and in the Material Safety Data Sheet. Wear proper protective equipment listed on the MSDS. Follow the instructions of your KML Representative in the proper use of this product.

ADVANTAGES:

- Provides excellent scale inhibition, ensuring maximum heat transfer efficiency
- Provides both oxygen and general corrosion inhibition
- Formulated for use as a boiler water additive in FDA & USDA Applications

Typical Product Characteristics

AppearanceLight yellow liquid
Density at 25°C1.12 – 1.14 g/ml
Weight per US gallon9.4 lbs./gal
pH of product> 12.5

PACKAGING:

BWT-209 is available in non-returnable, DOT approved, 55, 30 and 15-gallon plastic drums and 5-gallon plastic pails.

