

## **BWT-220**

### **SCALE INHIBITOR**

#### **DESCRIPTION:**

BWT-220 is a liquid blend of chelating agents and an anionic polymeric sludge conditioner. It is recommended for use as a dispersant in systems where low sludge volumes are required. BWT-220 may also be used to remove soft boiler deposits.

#### **GENERAL APPLICATIONS:**

Dosages will vary depending upon the type of boiler and the hardness level of the boiler feedwater. For optimum results, the recommendations of your KML Technical Representative should be followed.

#### **SAFETY & HANDLING:**

Improper handling of this product can be injurious to workers. Observe all safety precautions shown on the label and in the Material Safety Data Sheet. Wear proper protective equipment listed on the MSDS. Follow the instructions of your KML Representative in the proper use of this product.

#### **ADVANTAGES:**

- Effective dispersant and scale inhibitor
- Effective in soft scale removal
- Effectively reduces levels of boiler sludge

#### **Typical Product Characteristics**

Appearance .....Light yellow liquid  
Density at 25°C .....1.05 - 1.09 g/ml  
Weight per US gallon .....8.9 lbs/gal  
pH of product .....> 12.5

#### **PACKAGING:**

BWT-220 is available in non-returnable, DOT approved, 55, 30 and 15-gallon plastic drums and 5 gallon plastic pails.

