

BWT-23

CLOSED SYSTEM INHIBITOR

DESCRIPTION:

BWT-23 is a combination blend of a nitrite borate mild steel corrosion inhibitor and yellow metal corrosion inhibitors. BWT-23 provides complete corrosion for both hot and chilled closed systems.

GENERAL APPLICATIONS:

BWT-23 should initially be applied at a rate of 2.0 - 3.0 gallons for every 1000 gallons of water in the system. Periodic maintenance dosages may be required to maintain the desired nitrite treatment residual.

SAFETY & HANDLING:

Improper handling of this product can be injurious to workers. Observe all safety precautions shown on the label and in the Material Safety Data Sheet.

Wear proper protective equipment listed on the MSDS. Follow the instructions of your KML Representative in the proper use of this product.

ADVANTAGES:

- Does not contain chromates
- Simple control test
- Excellent corrosion inhibition in a wide range of temperatures
- Effective in environments high in iron content

Typical Product Characteristics

AppearancePale yellow liquid
Density at 25°C1.25 - 1.29 g/ml
Weight per US Gallon10.6 lbs/gal
pH of Product> 12.5

PACKAGING:

BWT-23 is available in non-returnable, DOT approved, 55, 30, and 15-gallon plastic drums and 5-gallon pails.

