

## **BWT-256**

### **POLYPHOSPHATE BOILER TREATMENT**

#### **DESCRIPTION:**

BWT-256 is a concentrated liquid blend of polyphosphates and a polymeric sludge conditioner. BWT-256 provides excellent corrosion and scale inhibition in one complete product. BWT-256 should be used in conjunction with an oxygen scavenger.

#### **GENERAL APPLICATIONS:**

Dosages will vary depending upon the level of hardness in the boiler feedwater. For optimum results, the recommendations of your KML Technical Representative should be followed.

#### **SAFETY & HANDLING:**

Improper handling of this product can be injurious to workers. Observe all safety precautions shown on the label and in the Material Safety Data Sheet. Wear proper protective equipment listed on the MSDS. Follow the instructions of your KML Representative in the proper use of this product.

#### **ADVANTAGES:**

- Provides corrosion and scale inhibition in one product
- Low, economical dosages
- Simple control test

#### **Typical Product Characteristics**

Appearance .....	Clear liquid
Density at 25°C .....	1.03 - 1.06 g/ml
Weight per US gallon .....	8.8 lbs./gal
pH of product .....	> 12.5

#### **PACKAGING:**

BWT-256 is available in non-returnable, DOT approved, 55, 30 and 15-gallon plastic drums and 5-gallon plastic pails.

