

BWT-258

POLYPHOSPHATE BOILER TREATMENT

DESCRIPTION:

BWT-258 is a concentrated liquid blend of polyphosphates, an alkali for hydroxyl alkalinity adjustment, and an anionic sludge conditioner. BWT-258 should be used in conjunction with an oxygen scavenger.

GENERAL APPLICATIONS:

Dosages will vary depending upon the level of hardness in the boiler feedwater. For optimum results, the recommendations of your KML Technical Representative should be followed.

SAFETY & HANDLING:

Improper handling of this product can be injurious to workers. Observe all safety precautions shown on the label and in the Material Safety Data Sheet. Wear proper protective equipment listed on the MSDS. Follow the instructions of your KML Representative in the proper use of this product.

ADVANTAGES:

- Conditions sludge for easy removal via bottom blowdown
- Provides excellent corrosion inhibition of boiler surfaces
- Simple control test
- Formulated for use as a boiler water additive in FDA & USDA Applications

Typical Product Characteristics

Appearance.....Clear-yellow liquid
Density at 25°C1.09 - 1.11 g/ml
Weight per US gallon9.2 lbs./gal
pH of product> 12.5

PACKAGING:

BWT-258 is available in non-returnable, DOT approved, 55, 30 and 15-gallon plastic drums and 5-gallon plastic pails.

