

BWT-822

SOLID CLOSED SYSTEM INHIBITOR

DESCRIPTION:

BWT-822 is a combination blend of an anionic sludge conditioner, a nitrite, borate, mild-steel, corrosion inhibitor and yellow metal corrosion inhibitors. BWT-822 provides complete corrosion and scale inhibition for both hot and chilled closed systems.

GENERAL APPLICATIONS:

BWT-822 should initially be applied at a rate of approximately one pound for every 100 gallons of water in the system. Periodic maintenance dosages may be required to maintain the desired nitrite treatment residual.

SAFETY & HANDLING:

Improper handling of this product can be injurious to workers. Observe all safety precautions shown on the label and in the Material Safety Data Sheet.

Wear proper protective equipment listed on the MSDS. Follow the instructions of your KML Representative in the proper use of this product.

ADVANTAGES:

- Does not contain chromates
- Simple control test
- Excellent corrosion inhibition in a wide range of temperatures

Typical Product Characteristics

Appearance	Tan to brown solid
Density at 25°C	90 lbs/ft ³
Weight per US Gallon	NA
Typical pH (1% Solution)	12

PACKAGING:

BWT-822 is available in 4 x 1 gallon containers per case. Case weighs 48 lbs. Follow MSDS directions. Properly stored product will remain effective 24 - 36 months. Store in cool, dry area.

