

Baffle Coat BC 263

PAINT SHOP COATING

DESCRIPTION:

Baffle Coat BC 263 is a thick paste that is designed to serve as a barrier coating. Baffle Coat BC 263 protects back sections and sub-structures water may contact.

GENERAL APPLICATIONS:

Baffle Coat BC 263 may be rolled, brushed or mopped on. Baffle Coat BC 263 is not intended to be diluted. For clean up, use mineral spirits.

SAFETY & HANDLING:

Improper handling of Baffle Coat BC 263 can be injurious to workers. May cause transient irritation to eyes. Flush with large amounts of water. If irritation persists, consult with physician.

Observe all safety precautions shown on the label and in the Material Safety Data Sheet. Wear proper protective equipment listed on the MSDS. Follow the instructions of your KML Representative in the proper use of this product.

ADVANTAGES:

- Will not dissolve in water
- One coat application designed specifically to adhere to and protect all substrates
- Resistant to solvents and paints
- Will not generate foam if introduced into paint sludge system
- Low VOC content

Typical Product Characteristics

Appearance	White paste
Odor	Mild
Specific Gravity	0.87
pH	NA
Flash Point	360°F

STORAGE:

Baffle Coat BC 263 should be stored away from strong oxidizing agents and strong acids. Store away from open flame. Store at room temperature and pressure. Keep container closed when not in use.