

Baffle Coat BC 273

SPRAYABLE PAINT SHOP COATING

DESCRIPTION:

Baffle Coat BC 273 is a sprayable barrier coating. Baffle Coat BC 273 protects back sections and sub-structures water may contact.

GENERAL APPLICATIONS:

Baffle Coat BC 273 should be sprayed on. Baffle Coat BC 273 is not intended to be diluted. For clean up, use mineral spirits.

SAFETY & HANDLING:

Improper handling of Baffle Coat BC 273 can be injurious to workers. May cause transient irritation to eyes. Flush with large amounts of water. If irritation persists, consult with physician.

Observe all safety precautions shown on the label and in the Material Safety Data Sheet. Wear proper protective equipment listed on the MSDS. Follow the instructions of your KML Representative in the proper use of this product.

ADVANTAGES:

- Will not dissolve in water
- One coat application designed specifically to adhere to and protect all substrates
- Resistant to solvents and paints
- Will not generate foam if introduced into paint sludge system
- Low VOC content

Typical Product Characteristics

| | |
|------------------------|-------------|
| Appearance | White paste |
| Odor | Mild |
| Specific Gravity | 0.87 |
| pH | NA |
| Flash Point | 360°F |

STORAGE:

Baffle Coat BC 273 should be stored away from strong oxidizing agents and strong acids. Store away from open flame. Store at room temperature and pressure. Keep container closed when not in use.

