

Booth Grease BC-286

SPRAYABLE PAINT SHOP COATING

DESCRIPTION:

Booth Grease BC 286 is a sprayable grease that is designed to serve as a barrier coating. Booth Grease BC 286 protects back sections, spraybooths and sub-structures water may contact.

GENERAL APPLICATION:

Booth Grease BC 286 should be sprayed on. Booth Grease BC 286 is designed to be use as received. Use mineral spirits for clean up of Booth Grease BC 286.

SAFETY & HANDLING:

Improper handling of Booth Grease BC 286 can be injurious to workers. May cause transient irritation to eyes. Flush with large amounts of water. If irritation persists, consult with physician.

Observe all safety precautions shown on the label and in the Material Safety Data Sheet. Wear proper protective equipment listed on the MSDS. Follow the instructions of your KML Representative in the proper use of this product.

ADVANTAGES:

- Will not dissolve in water
- One coat application designed specifically to adhere to and protect all substrates
- Resistant to solvents and paints
- Will not generate foam if introduced into paint sludge system
- Will withstand temperatures up to 150°F.

Typical Product Characteristics

Appearance	Amber Paste
Odor	Mild
Specific Gravity	0.89
pH	NA
Flash Point	560°F
V.O.C.	0.0 lbs./gal.

STORAGE:

Booth Grease BC 286 should be stored away from strong oxidizing agents and strong acids. Store away from open flame. Store at room temperature and pressure. Keep container closed when not in use.

