

## CWT-360

### PH CONTROL COOLING WATER INHIBITOR

#### DESCRIPTION:

CWT-360 is a complete, environmentally acceptable treatment for use in open recirculated cooling systems. CWT-360 contains an inorganic acid that controls alkalinity and allows the system to operate at a greater number of cycles of concentration. CWT-360 allows for increased operating efficiency while still providing excellent scale and corrosion inhibition.

#### GENERAL APPLICATIONS:

Average maintenance dosage requirement is two to four pints CWT-360 per 1,000 gallons of bleed. Dosage requirements will vary depending upon water quality and system operating conditions. For optimum results, the recommendations of your KML Technical Representative should be followed.

#### PACKAGING:

CWT-360 is available in non-returnable, DOT approved 55, 30, and 15 gallon plastic drums and in 5 gallon pails.

#### ADVANTAGES:

- Formulated without toxic chromates or heavy metals eliminating their disposal problems
- Provides both ferrous and yellow metal corrosion inhibition
- Disperses silt, mud and dirt, reducing possibility of under deposit corrosion
- Effective and stable over a wide range of temperatures and pH
- Simple control test

#### Typical Product Characteristics

Appearance .....Light yellow liquid  
Density at 25°C .....1.07 – 1.09 g/ml  
Weight per US gallon .....9.0 lbs./gal  
pH of product .....1 - 3

#### SAFETY & HANDLING:

Improper handling of this product can be injurious to workers. Observe all safety precautions shown on the label and in the Material Safety Data Sheet. Wear proper protective equipment listed on the MSDS. Follow the instructions of your KML Representative in the proper use of this product.