

CWT-504

HYDROCARBON DISPERSANT & PENETRANT

DESCRIPTION:

CWT-504 is a concentrated blend of organic penetrants and dispersants for use in maintaining clean surfaces in heat transfer equipment and cooling towers. CWT-504 may also be used in the cleaning of biofilms and solubilizing hydrocarbon foulants in industrial water systems. CWT-504 is particularly useful in controlling bacterial biofilms when used with conventional biocide products.

GENERAL APPLICATIONS:

Dosages will vary depending upon application and severity of the existing conditions. For optimum results, the recommendations of your KML Technical Representative should be followed.

SAFETY & HANDLING:

Improper handling of this product can be injurious to workers. Observe all safety precautions shown on the label and in the Material Safety Data Sheet. Wear proper protective equipment listed on the MSDS. Follow the instructions of your KML Representative in the proper use of this product.

ADVANTAGES:

- Effectively disperses hydrocarbon contaminants in closed and open recirculating systems
- Acts as a penetrant to increase efficiency of biocide treatments
- Reduces corrosion associated with deposits resulting from biofilms

Typical Product Characteristics

AppearanceClear amber liquid
Density at 25°C1.09 – 1.11 g/ml
Weight per US gallon9.2 lbs./gal
pH of product5 – 7.7

PACKAGING:

CWT-504 is available in non-returnable, DOT approved, 55, 30 and 15-gallon plastic drums and 5-gallon plastic pails.

