

CWT-900

SOLID ORGANIC DISPERSANT & PENETRANT

DESCRIPTION:

CWT-900 is an organic penetrant and dispersant for use in maintaining clean surfaces in heat transfer equipment and cooling towers. CWT-900 may also be used in the cleaning of fouled industrial water systems. CWT-900 is particularly useful in cleaning deposits that result from the production of alga and bacterial biofilms.

GENERAL APPLICATIONS:

Dosages will vary depending upon application and severity of the existing conditions. For optimum results, the recommendations of your KML Technical Representative should be followed.

SAFETY & HANDLING:

Improper handling of this product can be injurious to workers. Observe all safety precautions shown on the label and in the Material Safety Data Sheet. Wear proper protective equipment listed on the MSDS. Follow the instructions of your KML Representative in the proper use of this product.

ADVANTAGES:

- Effective in recirculating water clean-ups
- Acts as a penetrant to increase efficiency of biocide treatments
- Reduces corrosion associated with deposits resulting from biofilms

Typical Product Characteristics

AppearanceTan to brown solid
Density at 25°C82 lbs/ft³
Weight per US gallonNA
Typical pH (1% Solution)7 - 8

PACKAGING:

CWT-900 is available in non-returnable, one-gallon containers. The containers are packaged four (4) to a 44-pound case. Normal product shelf life is 24 – 36 months when stored in a cool, dry area.

