

Carrier Coat 170

COATING FOR ASSEMBLY PLANT CARRIERS

DESCRIPTION:

CC 170 is a non-chalking – water based – slurry coating designed to serve as a temporary coating for automobile carriers. Withstands the high temperatures incurred in ovens and is readily removable using high-pressure spray equipment.

USE INSTRUCTIONS:

CC 170 can be applied with a brush, roller or airless spray equipment. When using an airless sprayer, a pump ratio with a minimum of 25:1 is best suited. A tip size of .0020 - .0025” is recommended for airless applications. High-pressure water removal with minimum water pressure of 2500 psi is recommended.

SAFETY AND HANDLING:

CC 170 may cause transient irritation to eyes. Flush with large amounts of water, if irritation persists, consult with physician.

Observe all safety precautions shown on the label and in the Material Safety Data Sheet. Wear proper protective equipment listed on the MSDS. Follow the instructions of

your Representative in the proper use of this product.

ADVANTAGES:

- One coat application designed specifically to retard the penetration of high solid paints and solvents
- High solids formulation and fast cure time to allow for short time constraints
- Provides a hard, durable coating that will not flake or dust during use
- Unique formulation designed to be easily rinsed at high pressure using cold or hot water

Typical Product Characteristics

Appearance	White, thick Liquid
Odor	Bland
pH	10.3
Sp. Gravity	1.26
Flash Point	None

STORAGE:

CC 170 should be stored away from strong oxidizing agents and strong acids. Protect from freezing. Store at room temperature and pressure. Keep container closed when not in use.

