

# Clear Tacky CTBC 130/265 Spraybooth Coatings

## DESCRIPTION:

Clear Tacky CTBC is a clear water based liquid coating. Clear Tacky CTBC is designed to serve as a temporary coating for walls and windows inside a paint spraybooth. Clear Tacky CTBC-265 is a heavy-duty coating and should be used in clearcoat areas.

## GENERAL APPLICATIONS:

Brush, roller or airless spray equipment may be used to apply Clear Tacky CTBC. When using an airless sprayer, a pump ratio with a minimum rating of 20:1 is best suited, to result in a tip pressure of 1000 – 2500 psi. A tip size of .0013 - .0017” is recommended for airless applications. High-pressure water removal with minimum water pressure of 1500 psi.

## ADVANTAGES:

- One coat application designed to render a clear, tacky coating.
- Coating will withstand extended periods before removal.

- Product will not allow high-solid paints and solvents to penetrate through.
- Unique formulation designed to be easily rinsed with cold or hot water.

## Typical Product Characteristics

Appearance .....	Clear, viscous liquid
Odor .....	Bland
Specific Gravity .....	1.03
pH .....	10.0
Flash Point .....	None
V.O.C. ....	0.60

## SAFETY & HANDLING:

Improper handling of Clear Tacky CTBC can be injurious to workers. May cause transient irritation to eyes. Flush with large amounts of water. If irritation persists, consult with physician.

Observe all safety precautions shown on the label and in the Material Safety Data Sheet. Wear proper protective equipment listed on the MSDS. Follow the instructions of your KML Representative in the proper use of this product.

## STORAGE:

Clear Tacky CTBC should be stored at room temperature and should be protected from freezing.