

Detack 1303

PAINT DETACKIFIER

DESCRIPTION:

Detack 1303 is a complex mixture of inorganics and organic polymers. It is supplied as a clear to slightly hazy viscous liquid. Detack 1303 generally performs best in a pH range of 6.5 – 9.5.

GENERAL APPLICATIONS:

Detack 1303 is a cationic coagulant, which is effective in liquid/solid separation and in detackification processes. It is especially effective as a paint detackifier in water wash paint booths. Detack 1303 is also effective in coagulating some organic dispersions in water and process streams. However, the most cost-effective product should be selected based on a performance evaluation using the particular waste or process stream intended for treatment. Detack 1303 may be diluted up to 90% with water.

SAFETY & HANDLING:

Improper handling of this product can be injurious to workers. Observe all safety precautions shown on the label and in the Material Safety Data Sheet. Wear proper protective equipment listed on the MSDS.

Follow the instructions of your KML Representative in the proper use of this product.

ADVANTAGES:

- Concentrated formulation provides for low feed requirements
- Effective over a wide pH range
- Versatile, forgiving paint detackifier

Typical Product Characteristics

Appearance.....	Red – Brown Liquid
Density at 77oF.....	8.6 ± 0.1 ppg
Viscosity.....	1700 – 2200 cps
Freeze Point.....	30°F

PACKAGING:

Detack 1303 should be kept in a closed container. If frozen, warm to 60 - 80°F and agitate prior to use.

