

# EPOXY STRIP

## PAINT STRIPPER

### DESCRIPTION:

EPOXY STRIP is a blend of organic cleaning agents developed for the removal of a wide variety of high solids 1K and 2K paints as well as certain epoxies. EPOXY STRIP is formulated with thickeners to improve the cleaning of vertical glass, stainless steel and galvanized steel surfaces. Compatibility testing shows no deleterious effects on paint detackification treatments.

### GENERAL USE

#### INSTRUCTIONS:

EPOXY STRIP is easily applied as received by using an airless paint sprayer, pressure pot or roller. EPOXY STRIP should be allowed to dwell on the surfaces for 30 to 60 minutes. In areas of heavy build-up, EPOXY STRIP should be left on surface for a minimum of 60 minutes. If this length of time is prohibitive, agitate lightly with a bristle brush to assist in the paint removal. EPOXY STRIP may be easily rinsed off the surfaces by flushing with fresh warm or cold water, or may be scraped off with scraper blade.

### SPECIAL PRECAUTIONS:

Keep away from open flames and sparks. Use in well-ventilated area or use proper respirator and chemical resistant gloves.

### ADVANTAGES:

- Low odor
- Clings to vertical surfaces
- Non-chlorinated
- Removes both 1K and 2K paints

### Typical Product Characteristics

Appearance.....	Transparent
Odor.....	Mild Amine
VOC per US gallon.....	8.66 lbs./gal
pH (5% in water).....	9.3
Packaging.....	55 Gallon Drums 5 Gallon Pail

### SAFETY AND HANDLING:

Improper handling of this product can be injurious to workers. Observe all safety precautions shown on the label and Material Safety Data Sheets. Wear proper protective equipment listed on the MSDS. Follow the instructions of your Representative in the proper use of this product.