

# FLOOR SEALER FW 131

## PROTECTIVE COATING

### DESCRIPTION:

Floor Sealer FW 131 is a water based sealer and topcoat finish designed to enhance the appearance and chemical resistance of concrete floors. This product contains urethane resin to provide excellent wear. Floor Sealer FW 131 has been designed to be manually rolled, sprayed or brushed. It is a single coat, self-leveling system. Floor Sealer FW 131 has a dry time of less than 45 minutes. It provides a high gloss, mar resistant finish that is impervious to most solvents.

### GENERAL USE INSTRUCTIONS:

Floor Sealer FW 131 may be rolled, mopped or sprayed. The preferred application method is using a lambs wool applicator. For spraying, use a pressurized tank and spray nozzle assembly. Floor Sealer FW 131 should not be diluted prior to applying. Floor Sealer FW 131 may be applied in a single coat to provide excellent wear. It has good self-leveling characteristics to provide an even finish.

Floor Sealer FW 131 may be cleaned up using warm or hot water. Avoid prolonged or direct contact. May cause transient irritation to eyes. Follow first aid information on MSDS.

### ADVANTAGES:

- High gloss, mar resistant finish
- Quick dry time
- Self leveling, long lasting

### Typical Product Characteristics

Appearance .....	Opaque liquid
Odor .....	Faint Wax
Solids .....	20%
VOC .....	0.16 lbs/gal
Packaging .....	5 Gallon Pail 55 Gallon Drum

### SAFETY AND HANDLING:

Improper handling of this product can be injurious to workers. Observe all safety precautions shown on the label and Material Safety Data Sheets. Wear proper protective equipment listed on the MSDS. Follow the instructions of your KML Representative in the proper use of this product. Protect from freezing. If product freezes, allow to thaw at room temperature. Product can then be used.