

Mask Wash

HOT WATER MASK WASHER

DESCRIPTION:

Mask Wash is an all in one liquid product designed to remove paint that has accumulated on paint masking fixtures.

GENERAL USE INSTRUCTIONS:

Mask Wash is for use in heated, ventilated tanks or spray wash cabinets. The operating range is 10 – 25% by volume with water. The temperature range is 150-180°F. Do not exceed 205°F. For optimal performance, an in tank circulation educator system is recommended.

SAFETY AND HANDLING:

Mask Wash may cause transient irritation to eyes. Flush with large amounts of water, if irritation persists, consult with physician.

Store Mash Wash away from strong oxidizing agents and strong acids.

Improper handling of this product can be injurious to workers. Observe all safety precautions shown on the label and Material Safety Data Sheets. Follow the instructions of your KML

Representative in the proper use of this product.

ADVANTAGES:

- Convenient, all-in-one formulation.
- Contains no chlorinated solvents.
- Designed specifically to dissolve all water based and solvent-based paint that accumulates on paint masking fixtures and accessories.
- Highly concentrated, may be diluted with water.
- Will not generate foam.

Typical Product Characteristics

Appearance	Light Brown
Odor	Odorless
pH	9.0 – 10.0
Sp. Gravity	1.05
VOC (lbs./gal.)	0.0
Flash Point	None
Freeze Point	<32°F

