

Oven Coating Protecto EE

PROTECTIVE OVEN COATING

DESCRIPTION:

Protecto EE is coating designed for use to serve as a Tacky Oven Coating. Protecto EE will trap airborne contaminants inside the oven. Protecto EE is also designed to protect substrate from pre-mature oxidation or corrosion.

GENERAL USE

INSTRUCTIONS:

Protecto EE is designed to be rolled on to the surface. Protecto EE is not intended to be diluted.

To remove Protecto EE, use KML VersiClean 1231 or other suitable KML product should be utilized.

SAFETY AND HANDLING:

Protecto EE may cause transient irritation to eyes. Flush with large amounts of water, if irritation persists, consult with physician. Clean skin and hands with use of a waterless hand cleaner.

Improper handling of this product can be injurious to workers. Observe all safety precautions shown on the label

and Material Safety Data Sheets. Follow the instructions of your KML Representative in the proper use of this product.

ADVANTAGES:

- Will not dissolve in water.
- One coat application designed specifically to adhere to and protect all substrates.
- Resistant to solvents, paints and volatiles.
- Will remain tacky in temperatures to 350F.

Typical Product Characteristics

Appearance	Dark, brown liquid
Odor	Bland
pH	NA
Sp. Gravity	0.91
VOC (lbs./gal.)	0.0
Flash Point	330°F
Packaging	55 Gallon Drums

