

OVEN TACKY HT243

PAINT SHOP COATING

DESCRIPTION:

Oven Tacky HT243 is a coating designed for use to serve as a Tacky Oven/Flash off coating. This product is designed to trap all air born contaminates. Product is also designed to protect substrate from pre-mature oxidation, or corrosion.

GENERAL USE

INSTRUCTIONS:

Oven Tacky HT243 is designed to be rolled on to surface. Oven Tacky HT243 may be rolled onto aluminum foil which can be adhered to surface. Oven Tacky HT243 can be reapplied over old coating multiple times. To remove use Versiclean 1231 or solvent. Oven Tacky HT243 is not intended to be diluted. For clean up use mineral spirits or Versiclean 1231.

ADVANTAGES:

- Will not dissolve in water
- One coat application designed specifically to adhere to and protect substrates.

- Resistant to solvents, paints and volatiles
- Will remain tacky in temperatures up to 290°F.

Typical Product Characteristics

Appearance	Clear
Odor	Solvent
Specific Gravity	0.83
Flash Point	145°F
pH	N/A

SAFETY AND HANDLING:

Improper handling of this product can be injurious to workers. Observe all safety precautions shown on the label and Material Safety Data Sheets. Wear proper protective equipment listed on the MSDS. Store in an approved location. Keep away from sparks and temperatures above 120°F. Follow the instructions of your KML Representative in the proper use of this product.

