

PS 240

Paint Stripper

DESCRIPTION:

PS 240 is a solvent based, thick, organic cleaner designed to remove accumulated overspray from all surfaces within the paint spraybooth.

GENERAL USE INSTRUCTIONS:

Product may be applied by brush, roller or airless spray equipment. When using an airless sprayer, a pump ratio with a minimum rating of 5:1 is best suited. A tip size of .0028 - .0040" is recommended for airless application. May be rinsed with plant water pressure. Water temperature may be hot or cold.

ADVANTAGES:

- Specifically formulated to attack and dissolve high solids paints, including 1K and 2K isocyanate paint technologies.
- No foaming characteristics, and will not become destructive to booth water detackification system.
- Excellent adhesion characteristic to reduce usage.
- Low odor, and extended dwell time before rinse.

- Unique formulation designed to be easily rinsed with cold or hot water.

Typical Product Characteristics

Appearance	Clear Brown Liquid
Odor	Mild Solvent
Sp. Gravity	0.90
pH (10%)	8.5-9.5
V.O.C.	5.45
Flash Point	140°F

SAFETY AND HANDLING:

May cause irritation to eyes. Flush with large amounts of water, if irritation persists, consult with physician. Avoid inhalation. If in contact with skin some defatting and irritation may occur. PS 240 should be stored at room temperature and should be protected from freezing and sparks.

Improper handling of this product can be injurious to workers. Observe all safety precautions shown on the label and Material Safety Data Sheets. Wear proper protective equipment listed on the MSDS. Follow the instructions of your KML Representative in the proper use of this product.