

PS 260

Paint Stripper

DESCRIPTION:

PS 260 is a solvent based, thick, organic cleaner designed to remove accumulated overspray from all surfaces within the paint spraybooth.

GENERAL USE

INSTRUCTIONS:

Product may be applied by brush, roller, airless spray equipment or air diaphragm pump. When using an airless sprayer, a pump ratio with a minimum rating of 5:1 is best suited. A tip size of .0028 - .0040" is recommended for airless application. Operate air diaphragm pumps at a 1-1 ratio. May be rinsed with plant water pressure. Water temperature may be hot or cold.

ADVANTAGES:

- Specifically formulated to attack and dissolve high solids paints, including 1K and 2K isocyanate paint technologies.
- No foaming characteristics, and will not become destructive to booth water detackification system.
- Excellent adhesion characteristic to reduce usage

- Low odor, and extended dwell time of up to 80 minutes before rinse.
- Unique formulation designed to be easily rinsed with cold or hot water

Typical Product Characteristics

Appearance...	Clear Lt. Yellow Liquid
Odor	Solvent
Sp. Gravity	0.90
pH	NA
V.O.C.	6.35
Flash Point	145°F

SAFETY AND HANDLING:

May cause irritation to eyes. Flush with large amounts of water, if irritation persists, consult with physician. Avoid inhalation. If in contact with skin some defatting and irritation may occur. PS 260 should be stored at room temperature and should be protected from freezing and sparks.

Improper handling of this product can be injurious to workers. Observe all safety precautions shown on the label and Material Safety Data Sheets. Wear proper protective equipment listed on the MSDS. Follow the instructions of your KML Representative in the proper use of this product.