

PS 661

Paint Stripper- Low VOC

DESCRIPTION:

PS 661 is a blend of organic cleaning agents developed for the removal of a wide variety of high solids uncured paint overspray. PS 661 is formulated with thickeners to improve the cleaning of vertical glass, stainless steel and galvanized steel surfaces. Rapidly attacks most paints. Compatibility testing shows no deleterious effects on paint detackification treatments.

GENERAL USE

INSTRUCTIONS:

PS 661 is easily applied as received using an airless paint sprayer. May also be applied using pressure pot systems. PS 661 should be allowed to remain on surfaces for at least 5 minutes before rinsing. In areas of heavy build-up, longer contact times will improve performance. If this length of time is prohibitive, agitate lightly with a bristle brush to assist in the paint removal. PS 661 is easily rinsed off the surfaces by flushing with fresh warm or cold water at low to medium pressure.

SPECIAL PRECAUTIONS:

Store away from heat, sparks and open flames. Use in well-ventilated area. In confined areas, use a properly fit respirator and chemical resistant gloves.

ADVANTAGES:

- Moderate odor
- Reduced VOC's
- Clings to vertical surfaces
- Easy rinsing
- Compatible with paint detackification operations

Typical Product Characteristics

Appearance....	Thick Clear Lt. Amber
Odor.....	Solvent
VOC per US gallon.....	5.75 lbs./gal
pH (5% in water).....	9.5-10.5
Packaging.....	55 Gallon Drums Bulk

SAFETY AND HANDLING:

Improper handling of this product can be injurious to workers. Observe all safety precautions shown on the label and Material Safety Data Sheets. Wear proper protective equipment listed on the MSDS. Follow the instructions of your KML Representative in the proper use of this product.