

## **PT-451-RA**

### **STICKIES CONTROL AGENT**

#### **PRODUCT INFORMATION:**

PT-451-RA is a proprietary blend of polymers and mineral oil. It is supplied as a clear to slightly hazy, low viscosity liquid. PT-451-RA performs well over a pH range of 3.0 - 10.0.

#### **APPLICATION:**

PT-451-RA is a blend of organic polymers and mineral oil designed to control deposition of stickies on paper machines. PT-451-RA may be applied via showers to control stickies deposits on rolls and/or on suction box covers.

PT-451-RA should be metered by a positive displacement pump into the water supply to the appropriate shower(s). Normally, this will be the puddling shower on a roll or the lube shower ahead of a suction box. A static mixer in the shower water line downstream from the point of addition is recommended. The dosage of PT-451-RA will be from 5 - 15 ml/min per foot of roll length, depending on the severity of the problem.

#### **Typical Properties**

App: .....Clear to slightly hazy liquid  
Density @ 77° F.....6.8 lbs/gallon  
Activity.....100%

#### **STORAGE AND HANDLING:**

PT-451-RA should be stored in corrosion resistant containers at 40-100° F. In case of skin contact, flush with water. In case of eye contact, flush with water and seek medical attention. The shelf life of PT-451-RA is at least six months.

