

# **SODIUM HYPOCHLORITE 1250**

## **OXIDIZING BIOCIDES**

### **DESCRIPTION:**

Sodium Hypochlorite 1250 is a liquid oxidizing sanitizer for use in paint deaerification operations. Sodium Hypochlorite 1250 is highly effective in the control of offensive odors. Sodium Hypochlorite 1250 may be pumped into the paint removal system using conventional chemical feed equipment.

### **APPLICATION:**

Sodium Hypochlorite 1250 should be metered into systems to maintain a 0.5 to 1.0 ppm free chlorine residual for 6 to 8 hours. Application is most effective at the onset of odor problems. Sodium Hypochlorite 1250 should be applied in accordance with the instructions of your KML Sales Representative.

### **SAFETY AND HANDLING:**

Store Sodium Hypochlorite 1250 in vented, closed, clean, non-corrosive containers in a cool, dry location, away from direct sunlight. If containers become heated, the

containers should be vented to release decomposition products (mainly oxygen under normal decomposition).

Improper handling of this product can be injurious to workers. Observe all safety precautions shown on the label and in the Material Safety Data Sheet. Wear proper protective equipment listed on the MSDS. Follow the instructions of your KML Representative in the proper use of this product.

### **Typical Product Characteristics**

Appearance .....Light, yellow liquid  
Density at 25oC .....1.22 g/ml  
Sodium hypochlorite (by wt) ..12.5 %  
pH of product .....12.0

### **PACKAGING:**

Sodium Hypochlorite 1250 is available in non-returnable, DOT approved 55, 30, and 15 gallon plastic drums and in 5 gallon pails.

