

## **URESEAL**

### **URETHANE FLOOR SEALER**

#### **DESCRIPTION:**

Ure Seal is a urethane based, metal cross-linked polymer developed for today's most prestigious floors. It is recommended for use in establishing an initial seal on porous surfaces. Ure Seal is especially effective in sealing concrete and masonry surfaces. The durable nature of this product provides long lasting shine and ability to withstand heavy traffic and wear. For an ongoing preventative maintenance program, Ure Seal works best when topcoated with SuperSeal.

#### **USE INSTRUCTIONS:**

Make sure surface to be sealed is free from oils, greases or other contaminants to prevent delamination from occurring. Neutralize surface with mild acid if an alkaline cleaner is used to prepare the surface. Ure Seal may be applied using a saturated cotton mop or lambs wool applicator. Ure Seal is best applied over areas in a thin even coat. If floor is extremely damaged or worn, wait 30 minutes and apply a second coat.

#### **ADVANTAGES:**

- Excellent concrete sealing properties
- Excellent leveling properties
- Exceptionally long lasting protection
- High solids reduce maintenance time

#### **Typical Product Characteristics**

Appearance ....	White, Opaque Liquid
Solids .....	20%
Packaging .....	55 Gallon Drum

#### **SAFETY AND HANDLING:**

Improper handling of this product can be injurious to workers. Observe all safety precautions shown on the label and Material Safety Data Sheets. Wear proper protective equipment listed on the MSDS. Follow the instructions of your KML Representative in the proper use of this product.

