

## **Vola Mene 12**

### **STEAM LINE TREATMENT**

#### **DESCRIPTION:**

Vola Mene 12 is a flake Octadecylamine used to prevent corrosion in steam and condensate lines. Vola Mene 12 delivers corrosion protection via barrier inhibition of metal surfaces. This corrosion inhibition mechanism is especially desirable in systems with extensive steam line runs or in systems where there is a significant amount of oxygen intake through leaks.

#### **GENERAL APPLICATIONS:**

Dosages will vary depending upon the size of the steam system and the rate of steam production. For optimum results, the recommendations of your KML Technical Representative should be followed.

#### **PACKAGING & HANDLING:**

Vola Mene 12 is available in non-returnable, DOT approved, 65-gallon fiber containers.

#### **ADVANTAGES:**

- Provides excellent condensate system corrosion inhibition
- Acceptable for use as a boiler water additive under FDA regulations
- Low, economical dosage rate in an easy to use flake form

#### **Typical Product Characteristics**

Appearance .....White, waxy solid  
Density at 25°C .....0.79 g/ml  
Weight per US gallon .....6.59 lbs./gal  
pH of product .....NA

#### **SAFETY & HANDLING:**

Improper handling of this product can be injurious to workers. Observe all safety precautions shown on the label and in the Material Safety Data Sheet. Wear proper protective equipment listed on the MSDS. Follow the instructions of your KML Representative in the proper use of this product.

