

Vola Mene 16

STEAM LINE TREATMENT

DESCRIPTION:

Vola Mene 16 is a steam line treatment used to control corrosion in steam and condensate lines. Vola Mene 16 contains three different amines, which provide wide coverage of a condensate system. The amines in Vola Mene 16 neutralize the carbonic acid resulting from the condensation of carbon dioxide and steam in the condensate system.

The active ingredients comply with Section 173.310 of the Code of Federal Regulations for use as a boiler water additive where steam may contact food products other than milk or milk products.

GENERAL APPLICATIONS:

The maximum concentration in food processing applications is 50 ppm of product in the steam. Follow the recommendations of your KML Representative for optimum results.

PACKAGING:

Vola Mene 16 is available in non-returnable, DOT approved 55, 30, and 15-gallon plastic drums and 5-gallon pail.

ADVANTAGES:

- Combination amine blend provides greater coverage than a single amine product
- Provides excellent condensate system corrosion inhibition
- Formulated for use as a boiler water additive in FDA & USDA Applications

Typical Product Characteristics

Appearance.....Colorless liquid
Density at 25°C.....0.96 - 0.99 g/ml
Weight per US gallon.....8.1 lbs/gal
pH of product.....> 12.5

SAFETY & HANDLING:

Improper handling of this product can be injurious to workers. Observe all safety precautions shown on the label and in the Material Safety Data Sheet. Wear proper protective equipment listed on the MSDS. Follow the instructions of your KML Representative in the proper use of this product.

