

Vola Mene 3

STEAM LINE TREATMENT

DESCRIPTION:

Vola Mene 3 is a steam line treatment used to control corrosion in steam and condensate lines. Vola Mene 3 neutralizes the carbonic acid resulting from the condensation of carbon dioxide and steam in the condensate system.

The active ingredient complies with Section 173.310 of the Code of Federal Regulations for use as a boiler water additive where steam may contact food products other than milk or milk products.

GENERAL APPLICATIONS:

Dosages will vary depending upon the alkalinity of the boiler feedwater. The maximum allowable concentration in food processing applications is 182 ppm of product in the steam. For optimum results, the recommendations of your KML Technical Representative should be followed.

PACKAGING:

Vola Mene 3 is available in non-returnable, DOT approved 55, 30, and 15-gallon plastic drums and 5-gallon pail.

ADVANTAGES:

- Concentrated formulation provides low, economical dosages
- Provides excellent condensate system corrosion inhibition
- Formulated for use as a boiler water additive in FDA & USDA Applications

Typical Product Characteristics

| | |
|----------------------------|------------------|
| Appearance | Clear liquid |
| Density at 25°C | 0.99 – 1.01 g/ml |
| Weight per US gallon | 8.3 lbs./gal |
| pH of product | 10 - 12 |

SAFETY & HANDLING:

Improper handling of this product can be injurious to workers. Observe all safety precautions shown on the label and in the Material Safety Data Sheet. Wear proper protective equipment listed on the MSDS. Follow the instructions of your KML Representative in the proper use of this product.

