

## Vola Mene 5

### STEAM LINE TREATMENT

#### DESCRIPTION:

Vola Mene 5 is a steam line treatment used to control corrosion in steam and condensate lines. Vola Mene 5 neutralizes the carbonic acid resulting from the condensation of carbon dioxide steam in the condensate system.

The active ingredients comply with Section 173.310 of the Code of Federal Regulations for use as a boiler water additive where steam may contact food products other than milk or milk products.

#### GENERAL APPLICATIONS:

Dosages will vary depending upon the alkalinity of the boiler feedwater. The maximum allowable concentration in food processing applications is 50 ppm of product in the steam. For optimum results, the recommendations of your KML Technical Representative should be followed.

#### PACKAGING:

Vola Mene 5 is available in non-returnable, DOT approved 55, 30, and 15-gallon plastic drums and 5-gallon pail.

#### ADVANTAGES:

- Combination amine blend provides greater coverage than a single amine product
- Provides excellent condensate system corrosion inhibition
- Formulated for use as a boiler water additive in FDA & USDA Applications

#### Typical Product Characteristics

Appearance .....Colorless liquid  
Density at 25°C .....0.98 – 1.00 g/ml  
Weight per US gallon .....8.3 lbs./gal  
pH of product .....11 - 12

#### SAFETY & HANDLING:

Improper handling of this product can be injurious to workers. Observe all safety precautions shown on the label and in the Material Safety Data Sheet. Wear proper protective equipment listed on the MSDS. Follow the instructions of your KML Representative in the proper use of this product.

