

## WPBC 2178

### PAINT SHOP COATING

#### DESCRIPTION:

WPBC 2178 is a white water based peelable coating. WPBC 2178 is designed to serve as a temporary booth coating for the interior surfaces of spraybooth and may be used on floors.

#### GENERAL APPLICATIONS:

WPBC 2178 may be rolled, brushed or sprayed on. Apply WPBC 2178 with an airless pump 20:1 to 30:1 using a .0017 - .0030-inch tip. For best results, regulate the inbound air pressure to 2,000 psi. Product is not designed to be diluted, viscosity may be custom blended to accommodate application. For best results, coverage should render a minimum of 10 mils wet thickness film. WPBC 2178 cleans up with fresh water.

#### ADVANTAGES:

- Improves visual lighting
- One coat application designed specifically to provide good “hiding” characteristics
- Heavy-duty coating, can withstand extended periods prior to removal.

- Will not generate foam if introduced into paint sludge system

#### Typical Product Characteristics

Appearance .....	White Liquid
Odor .....	Slight Alcohol
Specific Gravity .....	0.97
pH .....	10.0
Flash Point .....	> 200°F
V.O.C. (lbs./gal.) .....	0.6
% Solids.....	32%

#### SAFETY AND HANDLING:

May cause transient irritation to eyes. Flush with large amounts of water, if irritation persists, consult with physician. Improper handling of this product can be injurious to workers. Observe all safety precautions shown on the label and Material Safety Data Sheets. Wear proper protective equipment listed on the MSDS. Follow the instructions of your KML Representative in the proper use of this product.

#### STORAGE:

WPBC 2178 should be stored away from strong oxidizing agents and strong acids. Store at room temperature and pressure. Keep container closed when not in use.