

# Weld Splatter Barrier Coat PC 213

## HIGH SOLIDS PROTECTIVE COATING FOR WELDING SPLATTER

### DESCRIPTION:

Barrier Coat PC 213 is a high solids protective coating that protects against weld splatter as well as all other contaminants that would mar surfaces that should be protected.

### GENERAL APPLICATIONS:

Barrier Coat PC 213 can be sprayed or rolled onto surfaces. Dries in 1-2 hours and forms a soft, clean – waxy coating over surfaces where applied. Barrier Coat PC 213 is easily removed with water, water spray or scraping.

### SAFETY & HANDLING:

Improper handling of Barrier Coat PC 213 can be injurious to workers. May cause transient irritation to eyes. Flush with large amounts of water. If irritation persists, consult with physician.

Observe all safety precautions shown on the label and in the Material Safety Data Sheet. Wear proper protective equipment listed on the MSDS. Follow the instructions of your KML Representative in the proper use of this product.

### ADVANTAGES:

- Protects against weld splatter
- Easy on – Easy off
- Dries in less than 2 hours
- Increases production – protects equipment

### Typical Product Characteristics

App.....	Clear/haze viscous liquid
Odor .....	None
Specific Gravity .....	1.07
pH .....	9.0
Flash Point .....	None
VOC Content .....	0.0 lbs./gal.

### STORAGE:

Store in original container. Protect from freezing.

