

White Coating

WTBC 347

PAINT SHOP COATING

DESCRIPTION:

WTBC 347 is a white water based tacky coating. WTBC 347 is designed to serve as a temporary booth coating for the interior surfaces of spraybooth and may be rinsed with water.

GENERAL APPLICATIONS:

WTBC 347 may be either rolled, brushed or sprayed on. Apply WTBC 347 with an airless pump 5:1 to 30:1 using a .0017 - .0030 inch tip. For best results, regulate the inbound air pressure to 500 psi.

Product is not designed to be diluted, viscosity may be custom blended to accommodate application.

For best results, coverage should render a minimum of 10 mils wet thickness film. WTBC 347 cleans up with fresh water.

ADVANTAGES:

- Improves visual lighting
- One coat application designed specifically to provide good “hiding” characteristics
- Remains tacky to trap airborne contaminants

- Designed to remain tacky up to 200F
- Will not generate foam if introduced into paint sludge system

Typical Product Characteristics

Appearance	White liquid
Odor	Bland
Specific Gravity	1.20
pH	10.0
Flash Point	None
V.O.C. (lbs./gal.)	0.21

SAFETY AND HANDLING:

May cause transient irritation to eyes. Flush with large amounts of water, if irritation persists, consult with physician. Improper handling of this product can be injurious to workers. Observe all safety precautions shown on the label and Material Safety Data Sheets. Wear proper protective equipment listed on the MSDS. Follow the instructions of your KML Representative in the proper use of this product.

STORAGE:

WTBC 347 should be stored away from strong oxidizing agents and strong acids. Store at room temperature and pressure. Keep container closed when not in use.