

White Tacky WTBC 505

White Tacky Booth Coating

DESCRIPTION:

WTBC 505 is a white, water based, tacky booth coating. WTBC 505 is designed to serve as a temporary booth coating for the interior surfaces of spraybooths and may be rinsed with water. Protects surfaces from paint overspray and traps airborne contaminants.

GENERAL APPLICATIONS:

WTBC 505 may be rolled, brushed or sprayed on. For spraying, apply WTBC 505 with an airless pump 5:1 to 30:1 using a .0017 - .0030-inch tip. For best results, regulate the inbound air pressure to 2500 psi. Product is designed to be applied as shipped. For best results, coverage should render a minimum of 10 mils wet thickness and a maximum 30-mil film. Heavier films will have a tendency to run or sag. WTBC 505 cleans up with fresh water. Product may also be easily scraped off.

ADVANTAGES:

- Improves visual lighting
- One coat application designed specifically to provide good “hiding” characteristics.

- Remains tacky to trap airborne contaminants.
- Designed to remain tacky up to 180F.
- Will not generate foam if introduced into paint sludge system

Typical Product Characteristics

Appearance	White liquid
Odor	Bland
Specific Gravity	1.20
pH	10.0
Flash Point	None
V.O.C. (lbs./gal.).....	.021

SAFETY AND HANDLING:

May cause transient irritation to eyes. Flush eyes with large amounts of water, if irritation persists, consult physician. Improper handling of this product can be injurious to workers. Observe all safety precautions shown on the label and Material Safety Data Sheets. Wear proper protective equipment listed on the MSDS. Follow the instructions of your Representative in the proper use of this product.

STORAGE:

WTBC 505 should be stored away from strong oxidizing agents and strong acids. Store at room temperature and pressure. Keep container closed when not in use.