

X-Wax

PROTECTIVE COATING/WAX/COSMOLINE REMOVER

DESCRIPTION:

X-Wax is primarily designed for the removal of wax-like protective coatings that cover parts and equipment prior, during and after shipment. X-Wax is a blend of specialized ingredients to rapidly penetrate, dissolve and emulsify these coatings. It is comprised of non-hazardous solvents and detergent emulsifiers in a reduced VOC blend.

GENERAL APPLICATIONS:

Spray or brush onto surface to be cleaned. Allow X-Wax to soak on surface for a sufficient period to enhance penetration. Wipe off or remove with water rinse. Warm or tap temperature and moderate pressure adequate.

SAFETY AND HANDLING:

Observe all safety precautions shown on the label and Material Safety Data Sheets. Wear proper protective equipment listed on the MSDS. Follow the instructions of your KML Representative in the proper use of this product.

ADVANTAGES:

- Rapid penetration
- Complete and thorough emulsification
- Harmless to all surfaces including painted surfaces
- Unique formulation designed to be easily rinsed with cold, warm or hot water

Typical Product Characteristics

Appearance	.Clear, pale yellow liquid
OdorCharacteristic orange
Specific Gravity0.88
pHNA
Flash Point120°F
V.O.C.4.40

STORAGE:

X-Wax should be stored at room temperature and away from heat, sparks and open flame.

